

Glydea® ULTRA 60

Technical Specifications



Quality Wholesale Window Coverings
 Contract • Hospitality • Healthcare • Residential
 ph 866-753-1113 email customerservice@porterpreston.com www.porterpreston.com

Motor part numbers

Glydea® ULTRA 60 RTS motor (with 10' cable and molded NEMA plug)	Part# 1246118
Glydea® ULTRA 60 DCT motor (with 10' cable and molded NEMA plug)	Part# 1246117
Glydea® ULTRA 60 Wired motor (5' long without plug)	Part# 1003160

Features overview

Glydea® ULTRA 60	
Motor unit main features	
Soft start	✓
Manual operation	✓
Automatic limits on end stop	✓
Soft stop	✓
Intermediate position	✓
Touch motion with 2 sensitivity settings	✓
Adjustable limits	✓
Speed control & adjustment	✓
Control options	
Dry Contact input via RJ12 Connector	✓
Dry Contact individual, group and master control	✓
Radio Technology Somfy® RTS	✓
SDN RS485 digital technology (two-way communication)	✓
Zigbee® (two-way communication) (DCT only)	✓
Tandem alternative	✓
Sun control	✓
Timer control	✓
Installation and setting features	
Programming with buttons on motor unit	✓
Programming with DCT Setting Tool (preferred)	✓
LED indicators	✓
Motor unit direction change	✓
Factory reset	✓
Inverse (top mount) mounting	✓
Tracks/Drapery Types	
One-way opening	✓
Center opening	✓
Asymmetric	✓
Multiple	✓
Pinch pleat	✓
Ripplefold® with overlap arm	✓
Ripplefold® with butt arm	✓
Accordia®	✓

Motorized track main characteristics

Glydea® ULTRA 60	
Power Supply	120V AC 50/60 HZ
Amperage	0.8 A
Average linear speed	Silent Mode: 2.95 in./s (7.5 cm/s) Standard Mode: 4.95 in./s - 7.86 in./s (12.5 cm/s - 20 cm/s)
Power consumption	96W (standby <1W)
Power cable type	3-wire cable with molded NEMA plug 4-wire cable (wired version only)
Control connector type (Dry Contact)	RJ12
DCT control circuit voltage	3.3V DC
Motor sound level	<38 dBA at silent mode
Certifications	c TUV us, CE
Track maximum length	36 ft. (10.9 m)
Maximum number of splices	2
Minimum bending radius	11.8 in. (30 cm)
Minimum curving radius	118 in. (300 cm)
Side opening max weight	132 lbs. 60 kg.
Center opening max weight	132 lbs. 60 kg.
Tandem alternative	264 lbs./ 120 kgs. 72 ft./ 21.8 m

Motor dimensions

